

# RemoteBridge Plugin Documentation

## REQUIREMENTS

- i-MSCP versions >= 1.1.0.rc4.7
- Bind must be activated on i-MSCP
- Domain for your RemoteBridge must use the nameserver of your i-MSCP installation

## INSTALLATION

- Login into the panel as admin and go to the plugin management interface
- Upload the RemoteBridge plugin archive
- Activate the plugin

## UPDATE

- Login into the panel as admin and go to the plugin management interface
- Upload the RemoteBridge plugin archive
- Update the plugin list through the plugin interface

## RemoteBridge URL

```
http(s)://admin.myserver.tld/remotebridge.php
```

## How to send data to the remote bridge (example)

```
function dataEncryption($dataToEncrypt, $ResellerUsername) {
    return strtr(base64_encode(mcrypt_encrypt(MCRYPT_RIJNDAEL_256,
md5($ResellerUsername), serialize($dataToEncrypt), MCRYPT_MODE_CBC,
md5(md5($ResellerUsername)))), '+/=', '-_');
}
$bridgeKey = '';
$ResellerUsername = '';

$dataToEncrypt = array(
    'action'              => '',
    'reseller_username'   => $ResellerUsername,
    'reseller_password'   => '',
    'bridge_key'          => $bridgeKey,
    'hosting_plan'        => '',
    'admin_pass'          => '',
    'email'               => '',
    'domain'              => ''
```

```
);

$ch = curl_init('http(s)://admin.myserver.tld/remotebrigde.php');
curl_setopt($ch, CURLOPT_POST, 1);
curl_setopt($ch, CURLOPT_POSTFIELDS,
'key='.$bridgeKey.'&data='.$dataEncryption($dataToEncrypt,
$ResellerUsername));
curl_setopt($ch, CURLOPT_RETURNTRANSFER, 1);

$httpResponse = curl_exec($ch);
echo $httpResponse;
curl_close($ch);
```

## Post data variables which are available / required

### key (required)

- This is your own bridge key

### data (required)

- This is a encrypted data array

## Encrypted array variables which are available / required

### 1. action (required)

- This actions are available: create, terminate, suspend, unsuspend, addalias

#### 1.1 action create

- creates a new i-MSCP account

#### 1.2 action terminate

- deletes an existing i-MSCP account

#### 1.3 action suspend

- disables an existing i-MSCP account

#### 1.4 action unsuspend

- enables an existing i-MSCP account

## 1.5 action addalias

- Adds a new domain alias to an existing i-MSCP account

## 2. reseller\_username (required)

- value: Username of the reseller account

## 3. reseller\_password (required)

- value: Password of the reseller account

## 4. domain (required)

- This will be later the new login of the i-MSCP panel

## 5. admin\_pass (required)

- Password for the new login of the i-MSCP panel

## 6. email (required)

- Emailadress for the new login of the i-MSCP panel

## 7. hosting\_plan (required if you want to use hosting plans to create a user)

- value: string of the hosting plan name

### 7.1 hp\_mail (required if hosting\_plan not set)

- value: -1 (disabled), 0 (unlimited) or a number > 0

### 7.2 hp\_ftp (required if hosting\_plan not set)

- value: -1 (disabled), 0 (unlimited) or a number > 0

### 7.3 hp\_traff (required if hosting\_plan not set)

- value: 0 (unlimited) or a number > 0 in MB

## **7.4 hp\_sql\_db (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

## **7.5 hp\_sql\_user (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

## **7.6 hp\_sub (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

## **7.7 hp\_disk (required if hosting\_plan not set)**

- value: 0 (unlimited) or a number > 0 in MB

## **7.8 hp\_als (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

## **7.9 hp\_php (required if hosting\_plan not set)**

- value: yes or no

## **7.10 hp\_cgi (required if hosting\_plan not set)**

- value: yes or no

## **7.11 hp\_backup (required if hosting\_plan not set)**

- value: no, dmn, sql or full

## **7.12 hp\_dns (required if hosting\_plan not set)**

- value: yes or no

## **7.13 hp\_allowsoftware (required if hosting\_plan not set)**

- value: yes or no (php must enabled if you set this value to yes)

## **7.14 external\_mail (required if hosting\_plan not set)**

- value: yes or no (hp\_mail does not set to hp\_mail -1)

## **7.15 web\_folder\_protection (required if hosting\_plan not set)**

- value: yes or no

## **7.16 phpini\_system (required if hosting\_plan not set)**

- value: yes or no

## **7.17 phpini\_perm\_allow\_url\_fopen (required if hosting\_plan not set)**

- value: yes or no

## **7.18 phpini\_perm\_display\_errors (required if hosting\_plan not set)**

- value: yes or no

## **7.19 phpini\_perm\_disable\_functions (required if hosting\_plan not set)**

- value: yes or no

## **7.20 phpini\_post\_max\_size (required if hosting\_plan not set)**

- value: numeric in MB

## **7.21 phpini\_upload\_max\_filesize (required if hosting\_plan not set)**

- value: numeric in MB

## **7.22 phpini\_max\_execution\_time (required if hosting\_plan not set)**

- value: numeric in seconds

## **7.23 phpini\_max\_input\_time (required if hosting\_plan not set)**

- value: numeric in seconds

## 7.24 phpini\_memory\_limit (required if hosting\_plan not set)

- value: numeric in MB

## 8. alias\_domains

- (must be an array), array('alias1.tld', 'alias2.tld')

## Encrypted array variables which are available / required

- fname: first name
- lname: last name
- firm: company
- zip: zipcode
- city: city
- state: state
- country: country
- phone: phone number
- fax: fax number
- street1: street
- street2: additional street informations
- gender: value can be "F=female, M=male"

## KNOWN ISSUES

From:

<https://wiki.i-mscp.net/> - i-MSCP Documentation

Permanent link:

<https://wiki.i-mscp.net/doku.php?id=plugins:remotebridge&rev=1390993218>

Last update: **2014/01/29 11:00**