ClamAV Plugin Documentation

Plugin allows to use ClamAV with i-MSCP.

Requirements

- i-MSCP versions >= 1.1.0
- Installed packages: clamav, clamav-base, clamav-daemon, clamav-freshclam, clamav-milter

Existing milter configurations

This plugin will not check for an existing milter configuration in the Postfix main.cf file. If you need to add an extra milter, please ask in our forum!

Installation

- 1. Install needed Debian/Ubuntu packages if not already done
- 1.1 Install the clamav packages

```
# aptitude update
# aptitude install clamav clamav-base clamav-daemon clamav-freshclam clamav-
milter
```

1.2 Stop the clamav-freshclam daemon if it is running

service clamav-freshclam stop

1.3 Update the virus database

freshclam

1.4 Start the clamav-freshclam daemon

```
# service clamav-freshclam start
```

1.5 Restart the clamav-daemon

- # service clamav-daemon restart
- 2. Get the plugin from github

cd /usr/local/src

git clone git://github.com/i-MSCP/plugins.git

3. Create new Plugin archive

```
# cd plugins
# tar cvzf ClamAV.tar.gz ClamAV
```

4. Plugin upload and installation

- Login into the panel as admin and go to the plugin management interface
- Upload the ClamAV plugin archive
- Install the plugin

Update

1. Get the plugin from github

```
# cd /usr/local/src
# git clone git://github.com/i-MSCP/plugins.git
```

2. Create new Plugin archive

```
# cd plugins
# tar cvzf ClamAV.tar.gz ClamAV
```

3. Backup your current plugin config

```
# plugins/ClamAV/config.php
```

4. Plugin upload and update

- Login into the panel as admin and go to the plugin management interface
- Upload the ClamAV plugin archive
- Update the plugin list

Configuration

For the different configuration options please check the plugin config file.

```
# plugins/ClamAV/config.php
```

After you made your config changes, don't forget to update the plugin list.

- Login into the panel as admin and go to the plugin management interface
- Update the plugin list

Testing

Eicar-Test-Signature

Send yourself a mail from another account (e.g. gmail or any other freemailer) with the following content in the message:

X50!P%@AP[4\PZX54(P^)7CC)7}\$EICAR-STANDARD-ANTIVIRUS-TEST-FILE!\$H+H*

Note that this should be reproduced in one line, without whitespace or line breaks.

Authors

- Sascha Bay info@space2place.de
- Rene Schuster mail@reneschuster.de

From: https://wiki.i-mscp.net/ - i-MSCP Documentation

Permanent link: https://wiki.i-mscp.net/doku.php?id=plugins:clamav&rev=1391124993

Last update: 2014/01/30 23:36

