

Plugin Configuration

Plugin Main Configuration Files

TODO

Plugin Local Configuration Files

Introduction

Most plugins provide a standardized configuration file (see above) which is located at root of their directory. This file is not persistent, meaning that on each plugin update, you'll have to backup and restore it once the new plugin version will be uploaded.

Because such behavior is not really convenient, the plugin API provide a way to create plugin local configuration files, which are automatically merged with the main configuration files. Those file are persistent and never deleted, even when i-MSCP get updated.

How It Works

When a local configuration file is found for a plugin, both, the default configuration file and the local configuration file are merged together.

Parameters defined in the local configuration files take precedence over those defined in default configuration files.

Creating Plugin Local Configuration File

All plugin local configuration file must be stored in the **imscp/gui/data/persistent/plugins** directory.

Local configuration files ***MUST*** be named with plugin name followed by the php file extension. For instance, if the plugin for which you want create a local configuration file is named JailKit, the local configuration file ***MUST*** be named **JailKit.php**

Plugin Local Configuration File Sample

Below a small sample of a plugin local configuration file which can help you to understand how this works.

Here we want override the following plugin main configuration file:

```
<?php
return array(
    // Jailkit installation directory.
    // This path is used as value of the --prefix option (JailKit configure
    // script).
    // IMPORTANT: You must never change this parameter while updating the
    // plugin to a new version.
    'install_path' => '/usr/local', // (Recommended value)

    // Full path to the root jail directory which holds all jails. Be sure
    // that the partition in which this directory is
    // living has enough space to host the jails.
    // IMPORTANT: You must never change this parameter while updating the
    // plugin to a new version.
    'root_jail_dir' => '/home/imscp-jails',

    // See man shells
    // Don't change this value if you do not know what you are doing
    'shell' => '/bin/bash', // (Recommended value)

    // See man jk_init
    'jail_app_sections' => array(
        'imscp-base', // Include Pre-selected sections, users and groups
        'mysql-client'
    ),

    // See man jk_cp
    // Any file which is not installed on your system will be ignored
    'jail_additional_apps' => array(
        '/bin/hostname',
        '/usr/bin/basename',
        '/usr/bin/dircolors',
        '/usr/bin dirname',
        '/usr/bin/clear_console',
        '/usr/bin/env',
        '/usr/bin/id',
        '/usr/bin/groups',
        '/usr/bin/lesspipe',
        '/usr/bin/tput',
        '/usr/bin/which'
    ),

    // See man jk_socketd
    'jail_socketd_base' => '512',
    'jail_socketd_peak' => '2048',
    'jail_socketd_interval' => '5.0'
);

```

We create the following local configuration file:

gui/data/persistent/plugins/JailKit.php file:

```
<?php
return array(
    // Override default jail root directory
    'root_jail_dir' => '/var/www/imscp-jails',

    // Append the git section to the jail_app_sections parameter
    'jail_app_sections' => array(
        'git'
    )
);
```

Important

Elements from default plugin configuration files are never removed automatically (this is by design). To remove an element, you must process as follow:

gui/data/persistent/plugins/JailKit.php file:

```
<?php
return array(
    '__OVERRIDE__' => array(
        // Override default jail root directory
        'root_jail_dir' => '/var/www/imscp-jails',

        // Append the git section to the jail_app_sections parameter
        'jail_app_sections' => array(
            'git'
        )
    ),
    '__REMOVE__' => array(
        // Remove mysql-client section from the jail_app_section parameter
        'jail_apps_sections' => array(
            'mysql-client'
        ),

        // Remove hostname command from the jail_additional_apps parameter
        'jail_additional_apps' => array(
            '/bin/hostname'
        )
    )
);
```

Here, the special array key **__OVERRIDE__** defines an array which contain elements to add/override, and the second special array key **__REMOVE__**, an array which contain elements to remove.

From:
<https://wiki.i-mscp.net/> - **i-MSCP Documentation**

Permanent link:
<https://wiki.i-mscp.net/doku.php?id=plugins:configuration&rev=1393096697> 

Last update: **2014/02/22 19:18**