

OpenDKIM Plugin Documentation

REQUIREMENTS

- i-MSCP versions \geq 1.1.0.rc4.7
- opendkim opendkim-tools Debian package

INSTALLATION

Ubuntu/Debian with aptitude

- apt-get opendkim opendkim-tools

Plugin installation

- Login into the panel as admin and go to the plugin management interface
- Upload the OpenDKIM plugin archive
- Activate the plugin

UPDATE

- Backup your current plugins/OpenDKIM/config.php file
- Login into the panel as admin and go to the plugin management interface
- Upload the OpenDKIM plugin archive
- Restore your plugins/OpenDKIM/config.php file (check for any change)
- Update the plugin list through the plugin interface

CONFIGURATION

Edit the plugins/OpenDKIM/config.php:

- opendkim_port \Rightarrow Port for the OpenDKIM daemon (don't use ports lower than 1000 and greater than 65535)
- opendkim_canonicalization \Rightarrow See code box below

Select the canonicalization method(s) to be used when signing messages. When verifying, the message's DKIM-Signature: header field specifies the canonicalization method. The recognized values are relaxed and simple as defined by the DKIM specification. The value may include two different canonicalizations separated by a slash ("/") character, in which case the first will be applied to the header and the second to the body. allowed values: simple (default), relaxed, simple/relaxed, relaxed/simple

- opendkim_trusted_hosts ⇒ Add domains which should be considered as trusted hosts by OpenDKIM

KNOWN ISSUES

From:
<https://wiki.i-mscp.net/> - **i-MSCP Documentation**

Permanent link:
<https://wiki.i-mscp.net/doku.php?id=plugins:opendkim&rev=1390993799>



Last update: **2014/01/29 11:09**