

# RemoteBridge Plugin Documentation

## REQUIREMENTS

- i-MSCP versions  $\geq$  1.1.0.rc4.7
- Bind must be activated on i-MSCP
- Domain for your RemoteBridge must use the nameserver of your i-MSCP installation

## INSTALLATION

- Login into the panel as admin and go to the plugin management interface
- Upload the RemoteBridge plugin archive
- Activate the plugin

## UPDATE

- Login into the panel as admin and go to the plugin management interface
- Upload the RemoteBridge plugin archive
- Update the plugin list through the plugin interface

## RemoteBridge URL

- <http://adminurl.tld/remotebbridge.php>

or

- <http://adminurl.tld/remotebbridge.php>

## How to send data to the remote bridge (example)

<https://github.com/i-MSCP/plugins/tree/master/RemoteBridge#how-to-send-data-to-the-remote-bridge-example>

## Post data variables which are available / required

### key (required)

- This is your own bridge key

**data (required)**

- This is a encrypted data array

**Encrypted array variables which are available / required****1. action (required)**

- This actions are available: create, terminate, suspend, unsuspend, addalias

**1.1 action create**

- creates a new i-MSCP account

**1.2 action terminate**

- deletes an existing i-MSCP account

**1.3 action suspend**

- disables an existing i-MSCP account

**1.4 action unsuspend**

- enables an existing i-MSCP account

**1.5 action addalias**

- Adds a new domain alias to an existing i-MSCP account

**2. reseller\_username (required)**

- value: Username of the reseller account

**3. reseller\_password (required)**

- value: Password of the reseller account

**4. domain (required)**

- This will be later the new login of the i-MSCP panel

## **5. admin\_pass (required)**

- Password for the new login of the i-MSCP panel

## **6. email (required)**

- Emailadress for the new login of the i-MSCP panel

## **7. hosting\_plan (required if you want to use hosting plans to create a user)**

- value: string of the hosting plan name

### **7.1 hp\_mail (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

### **7.2 hp\_ftp (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

### **7.3 hp\_traff (required if hosting\_plan not set)**

- value: 0 (unlimited) or a number > 0 in MB

### **7.4 hp\_sql\_db (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

### **7.5 hp\_sql\_user (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

### **7.6 hp\_sub (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

### **7.7 hp\_disk (required if hosting\_plan not set)**

- value: 0 (unlimited) or a number > 0 in MB

**7.8 hp\_als (required if hosting\_plan not set)**

- value: -1 (disabled), 0 (unlimited) or a number > 0

**7.9 hp\_php (required if hosting\_plan not set)**

- value: yes or no

**7.10 hp\_cgi (required if hosting\_plan not set)**

- value: yes or no

**7.11 hp\_backup (required if hosting\_plan not set)**

- value: no, dmn, sql or full

**7.12 hp\_dns (required if hosting\_plan not set)**

- value: yes or no

**7.13 hp\_allowsoftware (required if hosting\_plan not set)**

- value: yes or no (php must enabled if you set this value to yes)

**7.14 external\_mail (required if hosting\_plan not set)**

- value: yes or no (hp\_mail does not set to hp\_mail -1)

**7.15 web\_folder\_protection (required if hosting\_plan not set)**

- value: yes or no

**7.16 phpini\_system (required if hosting\_plan not set)**

- value: yes or no

**7.17 phpini\_perm\_allow\_url\_fopen (required if hosting\_plan not set)**

- value: yes or no

**7.18 phpini\_perm\_display\_errors (required if hosting\_plan not set)**

- value: yes or no

**7.19 phpini\_perm\_disable\_functions (required if hosting\_plan not set)**

- value: yes or no

**7.20 phpini\_post\_max\_size (required if hosting\_plan not set)**

- value: numeric in MB

**7.21 phpini\_upload\_max\_filesize (required if hosting\_plan not set)**

- value: numeric in MB

**7.22 phpini\_max\_execution\_time (required if hosting\_plan not set)**

- value: numeric in seconds

**7.23 phpini\_max\_input\_time (required if hosting\_plan not set)**

- value: numeric in seconds

**7.24 phpini\_memory\_limit (required if hosting\_plan not set)**

- value: numeric in MB

**8. alias\_domains**

- (must be an array), array('alias1.tld', 'alias2.tld')

**Encrypted array variables which are available / required**

- fname: first name
- lname: last name
- firm: company
- zip: zipcode
- city: city
- state: state
- country: country
- phone: phone number
- fax: fax number

- street1: street
- street2: additional street informations
- gender: value can be "F=female, M=male"

## KNOWN ISSUES

From:

<https://wiki.i-mscp.net/> - **i-MSCP Documentation**

Permanent link:

<https://wiki.i-mscp.net/doku.php?id=plugins:remotebridge&rev=1390992829>



Last update: **2014/01/29 10:53**